
## MEG

## WL22000VE/B 19,000 RUNNING WATTS

Rugged Steel Design -



—— B & S Commercial Vanguard Engine ——



Brushless Industrial Genend





—— LED Display —

Hours, RPMs, voltage, and frequency readings automatically cycle on the display.



Load Bars -

Easily verify the load balance on each leg of the generator end.




Warnings –

The LED will flash if any parameter gets outside of normal range. A warning will also be displayed when it is time for an oil change.



Receptacle Panel · with GFCI protection



## **SPECIFICATIONS**

· ENGIN	IE
ENGINE BRAND	BRIGGS & STRATTON
ENGINE MODEL	VANGUARD
ENGINE STARTER	ELECTRIC
ENGINE SPEED	3600 RPM
ENGINE CYLINDERS	V-TWIN
DISPLACEMENT/TYPE	993 CC / OHV
FREQUENCY REGULATION <sup>(1)</sup>	+/-1.5%
LOW OIL PROTECTION	STANDARD
RECOMMENDED OIL <sup>(2)</sup>	10W-30
OIL CAPACITY	2.3 QT
FUEL TANK	15 GAL
FUEL GAUGE	YES
FULL LOAD RUN TIME <sup>(3)</sup>	4.5 HOURS
FUEL CONSUMPTION 100% 75% 50% 25% 0%	GAL/HR 3.28 2.57 1.88 1.43 0.95
BATTERY SIZE <sup>(4)</sup>	BCI GROUP 26 500CCA
NOTES: (1) Steady state frequency regulation	12) The recommended oil is for

NOTES: (1) Steady state frequency regulation. (2) The recommended oil is for normal applications. See operator's manual for the recommended oil for your needs. (3) Run time is estimated. (4) Battery not included.

## ○ OPTIONAL ACCESSORIES ○

FOUR-WHEEL DOLLY KIT	WITH FLAT-FREE TIRES
COVER	45" x 32" x 30"
50A PLUG	CS6365C
30A PLUG	NEMA L14-30P
BATTERY	BCI GROUP 26 500 CCA
MAINTENANCE KIT	16200-011

•—— ELECT	RICAL ——
STARTING WATTS	22,000
RUNNING WATTS	19,000
RUNNING AMPS @ 120 VAC	158.3
RUNNING AMPS @ 240 VAC	79.2
VOLTAGE REGULATION	AVR +/- 1.5%
MAIN CIRCUIT BREAKER	80 AMP, 120/240V
BONDED NEUTRAL	YES
120 VOLT RECEPTACLES	(4) NEMA 5-20 20A (GFCI)
120/240 VOLT RECEPTACLES	(1) CS6365 50A (1) NEMA L14-30 30A (GFCI)
120/240 VOLT ANDERSON	120A
YOURGEN METER	STANDARD

•—— WL2200	0VE
MOTOR STARTING (CODE G)	6 HP
DBA @ 7 METERS	79
TOTAL HARMONIC DISTORTION	< 6%
LIFTING EYE <sup>(1)</sup>	STANDARD
4-WHEEL DOLLY KIT	OPTIONAL
INSULLATION	CLASS H
PROTECTIVE ROLL FRAME	1.25" DIA. 14 GA. STEEL
ASSEMBLED IN	USA
EPA APPROVED	YES
CARB APPROVED	NO
CSA APPROVED	NO
UNIT WARRANTY <sup>(2)</sup>	3 YEARS COMMERCIAL

NOTES: (1) Shipping eye shipped loose. (2) For more generator warranty, see operator's manual.

SHIPPING	
SHIPPING DIMENSIONS (L x W x H)	43.5" x 31" x 37"
SHIP WEIGHT	504 LBS
FREIGHT CLASS	70

28.85"



43"



28.85"



2.4

Specifications are subject to change without notice.

7/