



21.9LHO

	Rev: A		21.9L HO			
	Units		1500		1800	
	Std	Metric				
General Engine Data						
Type	N/A		V-type 4 cycle			
Number of cylinders	N/A		12			
Aspiration	N/A		Turbo Charge Air Cooled			
Bore	in	mm	5.04	128	5.04	128
Stroke	in	mm	5.59	142	5.59	142
Displacement	in^3	L	1338	21.9	1338	21.9
Compression Ratio	N/A		10.5			
Mean Piston Speed	ft/min	m/s	1398	7.1	1677	8.52
Gross Standby Power Rating^{1,2,3} Per ISO 3046 at the Flywheel						
NG	Hp	kW	507	378	649	484
LP	Hp	kW	370	276	471	351
MEP (@ rated Load on NG)	psi	bar	200	13.8	213	14.7
MEP (@ rated Load on LP)	psi	bar	146	10	155	11
Gross Prime Power Rating^{1,2,3} Per ISO 3046 at the Flywheel						
NG	Hp	kW	N/A	N/A	N/A	N/A
LP	Hp	kW	N/A	N/A	N/A	N/A
MEP (@ rated Load on NG)	psi	bar	N/A	N/A	N/A	N/A
MEP (@ rated Load on LP)	psi	bar	N/A	N/A	N/A	N/A
RPM Range (Min-Max)	RPM		1500-1800			
Rotation Viewed from Flywheel	N/A		Counter Clockwise			
Firing Order	N/A		1-12-5-8-3-10-6-7-2-11-4-9			
Dry Weight						
Fan to Flywheel	lb	kg	3638	1650	3638	1650
Rad to Flywheel	lb	kg	5238	2375.904	5238	2375.904
Wet Weight						
Fan to Flywheel	lb	kg	3813	1706	3813	1706
Rad to Flywheel	lb	kg	5760	2620	5760	2620
CG						
Distance from FW housing	in	mm	24	602	24	602
Distance above center of crankshaft	in	mm	7	182	7	182
Engine Mounting						
Maximum Allowable Bending Moment at Rear of Block	lb ft	N m				
Moment of Inertia About Roll Axis	lb ft^2	kg m^2				
Flywheel housing	N/A		SAE No.1			
Flywheel	N/A		No. 14			
Number of Flywheel Teeth	N/A		160			
Exhaust System						
Type			Water Cooled Manifold			
Maximum allowable Back pressure	in HG	kPa	3	10.2	3	10.2
Standard Catalyst Back pressure	in HG	kPa	1.5	5.1	1.5	5.1
Exhaust Outlet Pipe Size						
Maximum Turbine Inlet Temperature	F	C	1382	750	1382	750
Exhaust Flow at Rated Power	lb/hr	kg/hr	3184	1444	4286	1944
Exhaust Flow at Rated Power @1350F	cfm	m^3/min	2427	69	3179	90
Air Induction System						
Maximum allowable Intake Air Restriction with Air Cleaner						
Clean	inH2O	kPa	5	1.24	5	1.24
Dirty	inH2O	kPa	15	3.74	15	3.74
Combustion Air required	lb/hr	kg/hr	3004	1362	4044	1834
Combustion Air required	cfm	m^3/min	763	22	1027	29



21.9LHO

	Rev: A		21.9L HO			
	Units					
	Std	Metric	1500		1800	
Electrical System						
Minimum Recommended Battery Capacity	AH		200			
Cold Cranking Current						
Engine only	CCA		1000			
Engine with Drive train	CCA		1000			
Maximum Allowable Resistance of Starting Circuit	Ohms		0.002			
Starting Motor Power	HP	kW	9.4	7.0	9.4	7.0
Battery Charging Alternator						
Voltage	Volts		24			
Current	Amps		45			
Coil primary Resistance	Ohms		0.590 ± 10%			
Spark Plug p/n			IFR7F-4D			
Spark plug gap	inches	mm	.015" (-0/+0.008")		.38mm (-0/+2mm)	
Cooling System						
Coolant Capacity						
Engine only	gal	L	11.5	52.3	11.5	52.3
Engine with Radiator	gal	L	50.1	228	50.1	228
Engine Coolant Flow	gal/min	L/min	145	550	174	660
Water Pump Speed	RPM		2547		3056	
Heat rejected to Cooling water at rated Load	btu/min	kcal/sec	21451	90	27342	115
Maximum Intake Air Temperature (IAT)	F	C	155	68	155	68
ECU IAT Warning	F	C	140	60	140	60
ECU IAT Shutdown	F	C	155	69.10112	155	69.10112
Maximum Coolant Friction Head External to the engine	psi	bar	5.8	0.4	5.8	0.4
Maximum Air Restriction Across a Radiator	inH2O	mmH2O	0.5	12.8	0.5	12.8
Standard Thermostat Range						
Cracking Temperature	F	C	160	71	160	71
Full Open Temperature	F	C	185	85	185	85
Maximum Allowable Pressure Cap	psi	bar	14.7	1	14.7	1
Ambient Clearance Open Genset (water) (Air-to-Boil)						
Specified	F	C	142	61	142	61
Actual	F	C			142	61
Ambient Clearance (Oil)						
Specified	F	C	142	61	142	61
Actual	F	C			144	62
CAC Rise over Ambient (Charge)						
Specified	F	C	15	9	15	9
Actual	F	C			11	6
Maximum Allowable Top Tank Temperature	F	C	230	110	230	110
ECU Warning	F	C	220	104	220	104
ECU Shutdown	F	C	230	110	230	110
Fan Power	HP	kW	24	17.9	42	31.3
Fan Diameter, including blades	in	mm	52	1321	52	1321
Fan Speed	RPM		1200		1440	
Cooling Fan Air Flow @ 1" Static H2O Pressure and 125F @ radiator	CFM	m ³ /min	34,286	971	40,000	1,133
Charge Air Cooler						
Compressor Outlet Temperature	F	C	246	120	300	150
Compressor Flow Rate	lb/hr	kg/hr	3184	1444	4286	1944
Heat Rejection per CAC	btu/min	kW	TBD		3227	57



21.9LHO

	Rev: A		21.9L HO			
	Units		1500		1800	
	Std	Metric				
Lubrication System						
Oil Specification			SAE 15W-40 Low Ash Gas engine oil (.25-.5% by wt), API CD/CF or higher			
Oil Pressure						
Idle						
Min	Psi	Bar	13	0.9	13	0.9
Max	Psi	Bar	43.5	3	43.5	3
Rated Speed						
Min	Psi	Bar	43.5	3	43.5	3
Max	Psi	Bar	94.5	6.5	94.5	6.5
Maximum Allowable Oil Temperature	F	C	250	121	250	121
Engine Oil Capacity						
Min	Qts	L	34.75	33	34.75	33
Max	Qts	L	42.25	40	42.25	40
Oil Filter Capacity	Qts	L	7.5	7.1	7.5	7.1
ECU Oil Pressure Warning ⁵	psi		30			
ECU Oil Pressure Shut Down ⁵	psi		25			
Fuel System						
Fuel Consumption ⁶						
NG	Ft ³ /hr	kg/hr	3779	86	4490	102
LP	Ft ³ /hr	kg/hr	1186	63	1408	75
Maximum EPR Rated Pressure	psi	kPa	1.0	6.9	1.0	6.9
Maximum Running pressure to Electronic Pressure Regulator (EPR)	inH2O	kPa	11.0	2.7	11.0	2.7
Minimum Running pressure to EPR	inH2O	kPa	7.0	1.7	7.0	1.7
Minimum Gas Supply Pipe Size			2 x 2" NPT			
Maximum EPR Rated Pressure	psi	kPa	1.0	6.9	1.0	6.9
Maximum Running Pressure to EPR	inH2O	kPa	11.0	2.7	11.0	2.7
Minimum Running Pressure to EPR	inH2O	kPa	7.0	1.7	7.0	1.7
Minimum LPG Supply Pipe Size ⁴			2 x 2" NPT			
The preceding pipe sizes are only suggestions and piping sizes may vary with temperature, pressure, distance from supply and application of local codes. Gas must be available at adequate volume and pressure for engine at the EPR.						

¹Standby and overload ratings based on ISO3046.

² All ratings are gross flywheel horsepower corrected to 77°F at an altitude of 328feet with no cooling fan or alternator losses using heating value for NG of 1015 BTU/SCF.

³ Production tolerances in engines and installed components can account for power variations of +/- 5%. Altitude, temperature and excessive exhaust and intake restrictions should be applied to power calculations.

⁴ The preceding pipe sizes are only suggestions and piping sizes may vary with temperature, pressure, distance from supply and application of local codes. Gas must be available at adequate volume and pressure for engine at the EPR.

⁵ >1400RPM

⁶ See NGE Technical Spec. 56300002 - Fuel Specification